

USB-C ------COMPARISON CHART

In order to help users navigate their way around the different cables available today, we have created the '5-star' criteria system to rate and classify cables in line with the 5 most crucial operational aspects. On this page, you can find a short explanation of these criteria as well as what the corresponding star levels mean for each, and further on you can find our Comparison Chart including a wide range of cables and how they performed during our tests against these 5 criteria.



- 5 Stars



4K 60FPS Video and Audio 4-Lane DisplayPort

Alt mode



Mouse, Keyboard, Speakerphone, Thumb Drive and Webcam

> USB 2.0 480 Mbps "High Speed"



4K Webcam, SSD storage USB 3 Gen1 5 Gbps "SuperSpeed"



Fast Charging of Laptops, Tablets and Phones 60W / 3 A charging and eMarker



Convenient to use and to install

Connector dimensions according to standard; No bulky repeaters along the cable



Up to 4K60 (4-Lane DP)

Stable with all host

Stable with all hosts All wires are present At least 60 W PD support **AND**

Proper eMarker

Convenient to use and to install (No design flaws)



Up to 4K30 (2-Lane DP) Unstable with some hosts

Unstable with some hosts

PD supports less than 60W OR

Missing eMarker

At least one design flaw



No support

No support

Missing wires

No support

Missing wires

No PD support

No eMarker

Multiple design flaws











Recommended Cables for Taurus UCX Products

Most Important

Least Important

(USB-C to USB-C)		Length	Category	4K60 Video	USB 2.0	USB 3.	Charging + eMarker	Convenience	Comments	Rating
	Lightware CAB-USBC-100A/200A/300A	1 m / 2 m / 3 m	Copper	*	*	*	*	*		****
Recommended for Taurus UCX	Lightware CAB-USBC-T400B/500B	4 m / 5 m	Copper (MicroCoax)	*	*	*	*	*		****
	Atlona AT-LC-UC2UC-2M	2 m	Copper	*	*	*	*	*		****
	Freeport 26-715-06 (Extron)	1.8 m	Copper	*	*	*	*	*		****
	Delock 83668	2 m	Copper	*	*	*	*	*	Rigid cable	****
	TTL-Taiwan 20105	2 m	Copper	*	*	*	*	*	eMarker chip cannot be read; bigger cable head	***
	Bizlink KSC001R-16X	4 m	Active Copper	*	*	*	*	*	Only 4K30 video (2-lane DP Alt mode) supported	***
At your own risk	Extron USBC Pro/30	9,1m	Active optical	★	*	*	*	★	Only 4K30 video (2-lane DP Alt mode) supported; 2 Tier added at the USB2.0 topology, not recommended for complex USB systems	****
	Tether Tools CUC15	4,6 m	Copper	*	*	1	★	*	USB2.0 and USB3 lines does not work with some tested laptops*; only 30W charging power supported	***
	M-CAB 2200046	3 m	Copper	*	*	★	★	★	USB2.0 and USB3 lines does not work with some tested laptops*; Missing E-marker	***
	Freeport KFCB201208	4,5 m	Copper	*	★	★	★	★	USB2.0 and USB3 lines does not work with some tested laptops*; only 30W charging power supported	***
	Newnex U4SLC01C01-050	5 m	Copper	*	★	★	★	★	USB2.0 and USB3 lines does not work with some tested laptops*; Missing E-marker	***
	Cosemi 175USH31CCMM015M001	15 m	Active Optical	*	*	☆	*	☆	DP Alt mode only (no USB3 data); only 30W charging power supported	***

*tested hosts: Lenovo ThinkPad X280 Laptop; Dell G5 5587 Laptop.

These results were experienced with Lightware Taurus UCX product, your experience may vary.











Recommended Cables for Taurus UCX Products

Most Important

Least Important

USB-C to USB-C)		Length	Category	4K60 Video	USB 2.0	USB 3.	Charging + eMarker	Convenience	Comments	Rating
×	iiglo II-USBAMUSBC30-B300	3m	Copper	*	*	*	☆	*	USB3 lines does not work with some tested laptops*; only 30W charging power supported; Failed Total phase "Eye pattern" instrument test	***
No Video Not recommended for Taurus UCX with Taurus UCX	Club3D CAC-1535	5 m	Active Copper	*	☆	☆	*	\(\psi \)	4 lane DP Alt mode only (no USB3 and no USB2.0 data)	***
	Cable Matters 201034-BLK-5m	5 m	Active Copper	★	★	★	★	☆	USB2.0 and USB3 lines does not work with some tested laptops*; only 30W charging power supported; Amplifier in the middle	**
	Newnex ULK10G-CC-8M	8 m	Active Copper	★	*	★	★	☆	USB2.0 and USB3 lines does not work with some tested laptops*; only 30W charging power supported; Repeater in the middle, and quite rigid	**
	HP 9JH45AA	5 m	Active Copper	*	*	☆	☆	*	4 Iane DP Alt mode only (no USB3 data); USB2.0 lines does not work with some tested laptops*; only 30W charging power supported	**
	SmartAVLink SCVC-3100-20	20 m	Active Optical	*	$\stackrel{\wedge}{\Box}$	\Rightarrow	☆	☆	4 Iane DP Alt mode only (no USB3 and no USB2.0 data); No charging power	*
	Club3D CAC-1589	20 m	Active Optical	*	☆	$\stackrel{\wedge}{\Box}$	☆	☆	4 Iane DP Alt mode only (no USB3 and no USB2.0 data); No charging power	*
	Apple Thunderbolt 4 Pro Cable	1,8m / 3m	Active copper	☆	*	*	*	*	No DP Alt mode supported, therefore video and audio signals won't be transmitted for Taurus UCX	***
	SmartAVLink KUCC-3100-020	2 m	Copper	☆	*	*	★	*	No Video and Audio due to missing SuperSpeed wires; only 30W charging power supported	***
	Apple USB-C charge cable	1 m / 2m	Copper	☆	*	☆	*	*	No USB3 lines for video; For charging only	***
	Lanberg CA-CMCM-31CU-0030-BK	3m	Copper	☆	*	*	★	*	No USB3 lines for video; only 15W charging power supported; USB2.0 lines does not work with some tested laptops*	**

Cables that don't support video transmission are **not** 'host cables' by Lightware's definition!

*tested hosts: Lenovo ThinkPad X280 Laptop; Dell G5 5587 Laptop.

These results were experienced with Lightware Taurus UCX product, your experience may vary.





